2004-04-14

Status/Datum : LED 2005-03-30 .Typ : Q

Klassning

A method, system and receiver for receiving a multi-carrier signal where the

energy of the signal is defined in respect of an estimated guard interval position of

transform windom of said signal based on the determined energy.

IPC

ECLA, ICO, ECC

Övriga klasser

Sökord, engelska

guard+, w, interval, select, +, w, position+ (or, defin+, detect+, ), w, energy

transform, 3d, fourier+, fft

Sökord, övriga

pk 1-4, 7-23 WO 0169878 A1

pk 1-23 EP 0955754 A1

pk 1-23 WO 9917493 A1

pk 1-23

Litteratur

ţ,

2003-06-30 Ansökningsdatum

PALIN, Arto, VIIALA FI Uppfinnare Sökande

Berggren Oy AB, FIN-00101 Helsinki

Ombud

Ansvarskod

Titel

## A1AQ - ENGDAHL MARIANNE

# Faster fine timing operation in multi carrier system

#### H04L

### Egna länklappar

## Beskrivning

said signal and further that a position for a time domain to frequency domain

H04L27/26

H04L27/26M, H04L27/26M5C5

ofdm+, or, (orthogonal, w, frequency, w, division+)

dvb?, or, (digital, w, video, w, broad+)

Inter?symbol, w, interferenc+

EP 0837582 A2

US 5848107 A

Granskningstips

Nokia Corporation, FIN-02150 Espoo